



## SOLAR FLOODLIGHT 150W SYN-SYFLSOL0150



The Synerji Led Solar Floodlight is an efficient solution for rural or domestic applications, with an IP65 rating. It features a remote control with "Auto" (day / night mode), "on/off", "3H/5H/8H", "100%" and "50%" illumination functions. The Solar Panel charges the 3.2V 20AH Lithium Battery, requiring 6-8 hours of sunlight for a full charge. Discharge time on a full charge will be 8-9 hours on 50% and 5-7 hours on 100%. Important: For maximum battery charge efficiency, ensure the solar panel is positioned correctly (to enjoy morning and afternoon sun).

(DR) • (DF)	150W Solar Floodlight
	Nominal Power 10W
	1500 lm
	6500 k
5H	6 - 8 hrs charge time
	5 - 7 hrs discharge time (100%)
	8 - 9 hrs discharge time (50%)
	Solar Panel
	Peak Power 25W
· · · · · · · · · · · · · · · · · · ·	Rated Voltage 6V
	Rated Current 4.1A
	Short-circuit current 4.99A
9 9 9 9 9 9 7 mm 2 9	Open-circuit voltage 7.2V

## **Remote Control Features**

ON 1st press - circuit on 2nd press - light on	OFF Ligh	toff - Ċ	100% Illumination	֯:	50% illumination	+	Increase illumination	Decrease illumination
M Time control mode	3H Off a 3 hor		Off after 5 hours	8H	Off after 8 hours	AUTO	Activates day/night mode	
								OPERATING TEMPERATURE
							-20°	e ا أُنَّ ا ا ع
			This de intergra	vice is equip ated LED chi	pped with A*	LED	COLOUR TEMPER	RATURE: CRI: Raz
10000			sy		ríi 🔀	20		
			1	ELECTRICAL			WARM WHITE	COOL WHITE DAYLIGHT

E.&O.E.